



hanging grasspaper wallcoverings

This product should be hung by a professional paper hanger with experience of hanging textile wallcoverings. If you would like us to recommend someone, contact us on 01892 750003.

Occasional imperfections in yarn and weave are a natural characteristic of textile wallcoverings. Variations in tone can also appear within the roll and from roll to roll.

- | Prepare the wall surface such that it is normally absorbent.
- | Ensure that the walls are a similar colour to the wallcovering, particularly where it will make a joint.
- | Cut and mark drops in sequence from the roll.
- | As the joins are intended to be visible, and consequently each drop will appear as a panel, plan the layout of drops in advance to create a balanced overall effect
- | Bench trim a **minimum of 5cm** from the edge of each drop. (Alternatively, overlap and trim 5cm on the wall).
- | Damp the back of the wallcovering, and allow to rest for at least 3 minutes
Do not get water on face of the paper as it will stain.
- | Paste the wall with **Tapetex Pro – 1 adhesive**.
(Available from Stereo – contact details below)
- | Hang the drops as planned. Trim at skirting and ceiling. Butt join bench trimmed material or overlap and trim if not previously trimmed.
- | Do not get adhesive onto the face of the wallcovering as it cannot be wiped off.
- | After hanging 3 drops inspect the wallcovering to ensure you are happy with the results. If you have any doubts, stop hanging and contact us for advice.

STEREO
5 Bells Yew Green Business Centre, TN3 9BJ
Telephone: 01892 750003